FUSION LED COB 560 GEN 2 IP65

The introduction of our Fusion LED COB 560 brings another seamless lighting option to the Faze LED strip collection. Now Available with IP 65 allowing. This high quality, flexible COB strip can also be cut your required length here in our warehouse, all the way down to 50mm increments, ensuring that you receive the exact illumination for your project without any wastage.



FEATURES

- + High Quality, Flexible COB strip.
- + Available to order by the meter (Up to 10m & 15m).
- + Can be cut in 50mm increments.
- + 560 LEDs Per Meter.
- + 3M VHB Mounting Tape.
- + IP 65

	SDCM ≤2	120°	24V DC	\bigcirc
>54K Hrs IP 65	LED	CRI 90+	5	

GENERAL SPECIFICATIONS

LED	5W / m 10W / m	
Lumens Per Meter	384 lm 769 lm	
Efficacy Per Meter	Up to 77 lm/W	
Colour Temperature	3000K, Warm White4000K, Cool White	
Material	PCB	
Finish	White	
Beam	120°	
CRI	90+	
IP	65	
Colour Deviation	SDCM ≤2	
Lifetime	>54,000hrs L70 B10	
Warranty	5 Years	

PROJECT DETAILS

PROJECT:

TYPE:

NOTES:

DIMENSIONS



CUTTING LENGTHS		
5W	50mm Increments 15m Max Run Length	
10W	50mm Increments 10m Max Run Length	

PRODUCT CODES		
5W, 3000K	10-FSC2053IP	
5W, 4000K	10-FSC2054IP	
10W, 3000K	10-FSC2103IP	
10W, 4000K	10-FSC2104IP	

COMPATIBLE CASAMBI DEVICES

BasicDIM 24V Wireless 4ch	71-CAS24V
BasicDIM Driver 24V 150W	71-CAS24V150
BasicDIM Driver 24V 100W	71-CAS24V100
BasicDIM Driver 24V 60W	71-CAS24V60
BasicDIM Driver 24V 35W	71-CAS24V35

PROFILE OPTIONS					
Fusion H20	Fusion S17				
Fusion H30	Fusion A25				
Fusion S20	J Fusion R23				





1300 438 609 radiantlighting.com.au

ACCESSORIES

SOLDER STRIP IP 65 CONNECTION



Order Code

10-FSCONIP



