BLOC 1 FIXED

Introducing FAZE Bloc, the successor to the FAZE Dash series. With more customisability than ever before, the Bloc can fit into any space just the way you want it to.



PROJECT DETAILS

PROJECT:			
TYPE:			
NOTES:			

FEATURES

- + Deep set baffles keep glare to a minimum.
- + Featuring a shallow recess, the Bloc can fit into any environment.
- Using an OSRAM LED, the Bloc has great energy efficiency, and a long lifespan.
- Compatiable with remote Casambi CBU-TED Bluetooth Controllable Dimmer (71-CASCBU)



DIMENSIONS (L) Cut Out 37 x 37mm **H** 60mm W 45 x 45mm

GENERAL SPECIFICATIONS		
LED		2W
Lumens	(3000K) (4000K)	150 lm 170 lm
Efficacy		Up to 85 Lm/W
Colour Ter	mperature	3000K, Warm White 4000K, Cool White
Material		Powder Coated Aluminium
Finish		White Black
Beam		40°
CRI		90+
IP		20
Colour Deviation		SDCM ≤3
UGR		<19
Lifetime		>54,000hrs L80 B10
Warranty		5 Years
Please Note: When using C-Bus, user universal or		

GENERAL SPECIFICATIONS			
LED		2W	
Lumens	(3000K) (4000K)	150 lm 170 lm	
Efficacy		Up to 85 Lm/W	
Colour Tem	nperature	3000K, Warm White 4000K, Cool White	
Material		Powder Coated Aluminium	
Finish		White Black	
Beam		40°	
CRI		90+	
IP		20	
Colour Deviation		SDCM ≤3	
UGR		<19	
Lifetime		>54,000hrs L80 B10	
Warranty		5 Years	

DRIVER SPECIFICATIONS		
Power	700mA 2-5W Non-Dimmable Driver	
Dimming	Non-Dimming	
Driver Code	118-700MA5W	
Driver Sold Separately		

PRODUCT CODES		
White, 3000K, 2W	7-BLF102W403	
White, 4000K, 2W	7-BLF102W404	
Black, 3000K, 2W	7-BLF102B403	
Black, 4000K, 2W	7-BLF102B404	

ACCESSORIES		
Silver Baffle	7-BLBS	
Gold Baffle	7-BLBG	
White Baffle	7-BLBW	





trailing edge dimming modules.