

The BLOC linear downlight series delivers both flexibility and performance in any space. This recessed design is available in six sizes & two finishes with a fixed, adjustable or wall washer design.

FEATURES DIMENSIONS (mm) Cut Out + Deep set baffle for low glare 90x37mm + 40° beam + High CRI 🖸 60mm + Wide range of options available 45mm UGR SDCM () IP20 40° ≤3 <19 W 98mm G CRI 90+ 5 LED >54K **GENERAL SPECIFICATIONS DRIVER SPECIFICATIONS** LED 7W 700mA 5-12W Phase Cut Dimmable Driver Lumens 500 lm (3000K) | 520 lm (4000K) Efficacy 71 lm/w (3000K) | 74 lm/w (4000K) **Product Code:** 118-700MA12W 3000K, Warm White *Driver not included with fitting* **Colour Temperature** 4000K, Cool White Material **Powder Coated Aluminium** PRODUCT CODE White | Black Finish 7W, White, 3000K 7-BLF307W403 40° Beam 7-BLF307B403 7W, Black, 3000K CRI 90+ 7-BLF307W404 7W, White, 4000K IP 20 7-BLF307B404 7W, Black, 4000K SDCM ≤3 **Colour Deviation** 7-BLBS Silver Baffle <19 UGR Gold Baffle 7-BLBG Lifetime >54,000hrs L80 B10 Warranty 5 Years

TYPE:

NOTES:

www.radiantlighting.com.au	1300 438 609

radiantlighting