DISC

The Disc is designed with a diffused lens, creating a wide beam angle that is perfect for an even wash of light. Its powder croated aluminium fascia is available in 3 finishes.



PROJECT DETAILS

PROJECT:

TYPE:

NOTES:

1 Cut Out

Dimensions


Power

FEATURES

- + High quality diffuser for increased lumen output.
- + Specially designed heat sink for class leading heat dissipation.
- + IC-4 rated.
- + IP44 and suitable for wet areas.
- + Compatiable with remote Casambi CBU-TED Bluetooth Controllable Dimmer (71-CASCBU) & with Casambi BasicDim Driver (71-CAS600)



DIMENSIONS



DRIVER SPECIFICATIONS

L 104 x W 43 x H 24

300mA 240V Remote Dimmable Driver

GENERAL SPECIFICATIONS		
LED		12W
Lumens	(3000K) (4000K)	1040 lm 1070 lm
Efficacy		Up to 88 lm/W
Colour Temperature		3000K, Warm White 4000K, Cool White
Material		Powder Coated Aluminium
Finish		White Black Silver
Beam		90°
CRI		92+
IP		44
Colour Deviation		SDCM ≤3
UGR		<27
Lifetime		>54,000hrs L80 B10
Warranty		5 Years

Dimming	Phase Cut Dimming		
Power Factor	> 0.90		
DALI Dimming Available Upon Request			
DD	ADJUST CARES		
PRO	ODUCT CODES		
White, 3000K	118-DS5L12W903		
Black, 3000K	118-DS5L12B903		
Silver, 3000K	118-DS5L12S903		
White, 4000K	118-DS5L12W904		
Black, 4000K	118-DS5L12B904		
Silver, 4000K	118-DS5L12S904		



Please Note: When using C-Bus, user universal or

trailing edge dimming modules.

