EDGE 135

A clean finish every time - the EDGE 135 downlight is a larger version of the Edge 110, ideal for commercial projects. Utilising advancd LED engines, the Edge 135 achieves unmatched illumination with a fraction of the energy.



PROJECT DETAILS

PROJECT:

TYPE:

DIMENSIONS

NOTES:

FEATURES

- + Adjustable Head Up To 25°
- + Ideal For Commercial Projects.
- + Precision Reflector For Better Light Distribution And Performance.
- + Specially Designed Heat Sink For Class Leading Heat Dissipation.
- + Deep Set Lamp Position For Visual Comfort And Glare Control.
- + Compatible With Remote Casambi CBU-TED Bluetooth Controllable
- + Dimmer (71-CASCBU) & with Casambi BasicDim Driver 71-CAS600



© Ø135mm

GENERAL SPECIFICATIONS		
LED	25W	
Lumens	2255 lm (3000K) 2340 (4000K)	
Efficacy	Up to 92 lm/W	
Colour Temperature	3000K, Warm White 4000K, Cool White	
Material	Powder Coated Aluminium	
Finish	White Black	
Beam	60° 36° 24° 15°	
CRI	92+	
IP	44	
Colour Deviation	SDCM ≤2	
UGR	<19	
Lifetime	>55,000hrs L80 B10	
Warranty	7 Years	

DRIVER SPECIFICATIONS		
Dimensions	L 104 x W 43 x H 24 mm	
Power	600mA 240V Remote, Flicker Free Dimmable Driver	
Dimming	Phase Cut Dimming	
Power Factor	> 0.90	
DALL Dimensing Available Unan Beguest		

DALI Dimming Available Upon Request

	PRODUCT CODES
White, 3000K	118-ED2C25W603
Black, 3000K	118-ED2C25B603
White, 4000K	118-ED2C25W604
Black, 4000K	118-ED2C25B604

	REFLECTOR CODES
15° Reflector	118-RFLE15
24° Reflector	118-RFLE24
36° Reflector	118-RFLE36





Please Note: When using C-Bus, user universal or

trailing edge dimming modules.