## **LINE OPAL**

The Line Opal series is practical and stylish. With numerous mounting and design options, they provide flexibility across both residential and commercial projects.

## **PROJECT DETAILS**

PROJECT: TYPE: NOTES:

**DIMENSIONS** 

## **FEATURES**

- + Surfaced Mounted or Suspended Options.
- + Ceiling Canopy Specifically Designed For Seamless Installation.
- Surface Mount Option has 3mm detail from ceiling once installed.
- 1-10V Dimming & Non-Dimming Versions Available Upon Request.
- + Compatible with Remote Casambi CBU-TED Bluetooth Controllable Dimmer (71-CASCBU)

GENERAL SPECIFICATIONS



## **1** 70mm ■ 600mm | 1200mm | 1800mm | 2400mm **W** 41mm

**W** Ø80mm

☐] **(II)** 30mm

	OLIVE	IVAL 3		AIICIV	
LED		15W	30W	45W	60W
Lumens	(3000K) (4000K)		2300Lm 2424Lm		
Efficacy	(3000K) (4000K)	80Lm/W 82Lm/W	76Lm/W 81Lm/W	002, 11	7 0 2, 11
Colour <sup>-</sup>	Temperati	ıre	3000K, Warm White 4000K, Cool White		
Material			Powder Coated Aluminium		
Finish			White I Black		
Beam			90°		
CRI			90+		
IP			40		
UGR			21		
Colour Deviation			SDCM ≤3		
Lifetime			>60,000hrs L80 B10		
Warranty			5 Years		
Suspension Cable Length			(600m, 1200mm, 1800mm) 2m (2400mm) 1650mm		

DRIVER SPECIFICATIONS				
Power	600mA   1200mA   1800mA   2400mA 240V Built-In, Flicker Free, Dimmable Driver			
Dimming	Phase Cut Dimming			
Power Factor	> 0.90			

PRODUCT CODES						
600mm						
Black, 3000K	7-LI410615B903	Black, 4000K	7-LI410615B904			
White, 3000K	7-LI410615W903	White, 4000K	7-LI410615W904			
1200mm						
Black, 3000K	7-LI411230B903	Black, 4000K	7-LI411230B904			
White, 3000K	7-LI411230W903	White, 4000K	7-LI411230W904			
1800mm						
Black, 3000K	7-LI411845B903	Black, 4000K	7-LI411845B904			
White, 3000K	7-LI411845W903	White, 4000K	7-LI411845W904			
2400mm						
Black, 3000K	7-LI412460B903	Black, 4000K	7-LI412460B904			
White, 3000K	7-LI412460W903	White, 4000K	7-LI412460W904			



