


CORE G3

The Core ceiling light simultaneously creates a stylish feature whilst also providing sufficient task lighting. The silhouette is modern yet timeless and serves as a decorative alternative to your standard downlight. Ideal for areas with limited ceiling space.

- Generation 3 LED – Improved light output and efficiency.
- Flicker Free Driver.
- High CRI – Defining architectural details, and bringing finishes to life.
- Available in 3 beam angles – For the perfect light application.
- Multiple baffle options – Further aesthetic freedom and flare reduction.
- Quick connection system – For durability and easy installation.



DIMENSIONS **W** Ø95mm **H** 150mm

LUMINAIRE OPTIONS

BEAM OPTIONS

60° **STANDARD** 40° 20°

FINISHES

WHITE BLACK

BAFFLE FINISHES

BLACK **STANDARD** WHITE GOLD

IP OPTIONS

20 **STANDARD** 44

GENERAL SPECIFICATIONS

LED	LUMENS (3000K 4000K)
18W	1800 lm 1900 lm
EFFICACY	Up to 105 Lm/W
COLOUR	3000K, Warm White 4000K, Cool White
MATERIAL	Powder Coated Material
CRI	92+
IP	20
COLOUR DEVIATION	SDCM ≤2
UGR	<18
LIFETIME	> 55,000hrs L80B10
WARRANTY	5 Years

DRIVER SPECIFICATIONS

POWER	450mA 240V Built-In Flicker Free Driver
DIMMING	Phase Cut Dimming / DALI
POWER FACTOR	> 0.95

PROJECT DETAILS

PROJECT

TYPE

NOTES

PRODUCT CODES

White, 3000K	118-COR318W603
White, 4000K	118-COR318W604
Black, 3000K	118-COR318B603
Black, 4000K	118-COR318B604
White, 3000K, DALI	118-COR318W603D
White, 4000K, DALI	118-COR318W604D
Black, 3000K, DALI	118-COR318B603D
Black, 4000K, DALI	118-COR318B604D

ACCESSORIES

40° Reflector	118-LSCX40
20° Reflector	118-LSCX20
White Baffle	118-CORXSBW
Gold Baffle	118-CORXSBG
White, IP 44 Mounting Plate	118-CORIPKITW
Black, IP 44 Mounting Plate	118-CORIPKITB

