

CORE MINI TRACK

Minimal, functional and versatile; the Core Mini Track provides an ideal lighting solution for accent lighting in both residential and commercial applications.

- High CRI – Defining architectural details and finishes.
- Quick connection system – For durability and easy installation.
- Flicker free driver – To prevent eye strain.
- Available in 4 beam angles – For the perfect light application.
- Face it in any direction – Adjustable up to 90°, with a 350° rotation.
- Multiple finishes and baffle options to suit any aesthetic.



DIMENSIONS	H1 140mm	W1 Ø55mm	
DRIVER DIMENSIONS	H2 40mm	W2 170mm	D 31mm
HEIGHT FROM TRACK	H3 175mm		

LUMINAIRE OPTIONS

BEAM OPTIONS (REFLECTOR / LENS)

60° REFLECTOR **STANDARD** 60° 36° 24° 15°

FINISHES

☐ WHITE ☒ BLACK

GENERAL SPECIFICATIONS

LED	LUMENS (3000K 4000K)
11W	1140 lm 1200 lm
EFFICACY	Up to 109 Lm/W
COLOUR	3000K, Warm White 4000K, Cool White
MATERIAL	Powder Coated Aluminium
CRI	92+
IP	20
COLOUR DEVIATION	SDCM ≤2
UGR	<16
LIFETIME	> 55,000hrs L80B10
WARRANTY	5 Years

DRIVER SPECIFICATIONS

POWER	350mA 240V Built-In, Dimmable Driver
DIMMING	Phase Cut Dimming
POWER FACTOR	> 0.95

PROJECT DETAILS

PROJECT

TYPE

NOTES

	PRODUCT CODES
White, 3000K	118-COTM311W603
White, 4000K	118-COTM311W604
Black, 3000K	118-COTM311B603
Black, 4000K	118-COTM311B604
White, 3000K, DALI	118-COTM311W603D
White, 4000K, DALI	118-COTM311W604D
Black, 3000K, DALI	118-COTM311B603D
Black, 4000K, DALI	118-COTM311B604D



ACCESSORIES

36° Reflector	118-RFLE336
24° Reflector	118-RFLE324
15° Reflector	118-RFLE315
60° Lens	118-LSE360
36° Lens	118-LSE336
24° Lens	118-LSE324
15° Lens	118-LSE315



3 CIRCUIT TRACK COMPONENTS

3 Circuit Track Piece



DESCRIPTION

3 circuit track, available in 1m or 2m lengths.

H 32.5mm W 31.5mm



FINISHES

- 1m, White
- 1m, Black
- 2m, White
- 2m, Black

PRODUCT CODE

- 83-3C1MW
- 83-3C1MB
- 83-3C2MW
- 83-3C2MB

3 Circuit Recessed Track Piece




3 circuit recessed track, available in 1m or 2m lengths.

H 32.5mm W1 31.5mm W2 56mm

- 1m, White
- 1m, Black
- 2m, White
- 2m, Black

- 83-3CR1MW
- 83-3CR1MB
- 83-3CR2MW
- 83-3CR2MB

Feed Piece



The feed piece connects at the start of the track and supplies power to the entire track configuration.

W1 66mm W2 105mm

- White
- Black

- 83-3CFPW
- 83-3CFPB

Dead End




The dead end connects at the end of the track and completes the track with a clean finish.

W1 3mm W2 21mm

- White
- Black

- 83-3CDEW
- 83-3CDEB

Straight Connector




The straight connector joins two separate pieces of track together.

W 68mm

- White
- Black

- 83-3CSCW
- 83-3CSCB

Straight Connector Feed



The straight connector feed connects in the middle of two track pieces and supplies power to the entire track configuration. You can use a straight connector feed instead of a regular feed piece.

W1 100mm W2 166mm













- White
- Black

- 83-3CSFW
- 83-3CSFB

Please Note:

3 circuit recessed track is configured using the same components as the standard 3 circuit track. However in addition to this, cover plates are required. Please get in touch with one of our design consultants for more information.

3 CIRCUIT TRACK COMPONENTS

Corner Connector		DESCRIPTION	FINISHES	PRODUCT CODE
		<p>The corner connector is used to connect two pieces of track in a corner configuration. These pieces are available in both right and left configurations. A corner connector can also provide power to the track.</p> <p>H2 W 99mm H1 66mm</p>	<div> <div></div> Left, White <div></div> Left, Black <div></div> Right, White <div></div> Right, Black </div>	83-3CLCW 83-3CLCB 83-3CRCW 83-3CRCB
T Connector		DESCRIPTION	FINISHES	PRODUCT CODE
		<p>The T Connector is used to connect three pieces of track in a T configuration. The T Connector can also supply power to the track. Available in left and right configurations.</p> <p>H1 66mm H2 99mm W1 100mm W2 166mm</p>	<div> <div></div> Left, White <div></div> Left, Black <div></div> Right, White <div></div> Right, Black </div>	83-3CTLCW 83-3CTLCB 83-3CTRCW 83-3CTRCB
Cross Connector		DESCRIPTION	FINISHES	PRODUCT CODE
		<p>The cross connector is used to connect four pieces of track in a cross configuration. The cross connector also supplies power to the track.</p> <p>H1 100mm H2 166mm W1 100mm W2 166mm</p>	<div> <div></div> White <div></div> Black </div>	83-3CCCW 83-3CCCB
Adaptor		DESCRIPTION	FINISHES	PRODUCT CODE
		<p>The adaptor is a clip-in component which comes as standard on every FAZE track fitting. The adaptor is used to connect the luminaire to the track.</p> <p>The adaptor can carry fittings of 5kg or less.</p> <p>H 39mm W 30mm</p>	<div> <div></div> White <div></div> Black </div>	83-3CCCW 83-3CCCB
Wire Suspension Kit		DESCRIPTION	FINISHES	PRODUCT CODE
		<p>The wire suspension kit is used to suspend the track configuration.</p>	<div> <div></div> White <div></div> Black <div></div> Silver </div>	83-3CWSUPW 83-3CWSUPB 83-3CWSUP
Universal Fixing Piece		DESCRIPTION	FINISHES	PRODUCT CODE
		<p>The universal fixing piece can be used to mount the track in a fixed position.</p>	<div> <div></div> White <div></div> Black </div>	83-3CUFW 83-3CUFB

Please Note:

3 circuit recessed track is configured using the same components as the standard 3 circuit track. However in addition to this, cover plates are required. Please get in touch with one of our design consultants for more information.