
CORE XS

The CORE XS simultaneously creates a stylish feature whilst also providing sufficient task lighting. An ideal luminaire for areas with limited ceiling space.

- High CRI Defining architectural details and finishes.
- Quick connection system For durability and easy installation.
- Flicker free driver To prevent eye strain.
- Available in 3 beam angles For the perfect light application.
- High quality lenses For superior light emissions.



PROJECT DETAILS



LUMINAIRE OPTIONS BEAM OPTIONS 60° STANDARD 40° 20° FINISHES WHITE BLACK		
60° STANDARD 40° 20° FINISHES	LUMINAIF	RE OPTIONS
FINISHES	BEAM OPTIONS	
	60° STANDARD 40° 20°	
WHITE BLACK	FINISHES	
	WHITE BLACK	

GENERAL SPECIFICATIONS		
LED	LUMENS (3000K 4000K)	
11W	1200 lm 1300 lm	
EFFICACY	Up to 118 Lm/W	
COLOUR	3000K, Warm White 4000K, Cool White	
MATERIAL	Powder Coated Aluminium	
FINISH	White Black	
CRI	92+	
IP	20	
COLOUR DEVIATION	SDCM ≤2	
UGR	<18	
LIFETIME	> 55,000hrs L80B10	
WARRANTY	5 Years	

	DRIVER SPECIFICATIONS
POWER	300mA 240V Built-In Driver
DIMMING	Phase-Cut
POWER FACTOR	> 0.95

	PRODUCT CODES	
White, 3000K, 60°	118-CORXS11W603	
White, 4000K, 60°	118-CORXS11W604	
Black, 3000K, 60°	118-CORXS11B603	
Black, 4000K, 60°	118-CORXS11B604	

	ACCESSORIES	
40° Lens	118-LSCX40	
20° Lens	118-LSCX20	



