

EDGE 100

Incorporating a minimal trim design, with advanced LED engines to achieve intense illumination with a high lumen per watt efficacy.

- Adjustable head up to 25°.
- Precision reflector with clear lens – for better light distribution.
- Specially designed heat sink – for class leading heat dissipation.
- Deep set lamp position – for visual comfort and glare reduction.
- Suitable for concrete installation – concrete cannister sold separately.
- Next-Gen LED chip technology.



DIMENSIONS W Ø100 mm H 115 mm

CUT-OUT Ø92mm

LUMINAIRE OPTIONS

LED & LUMENS OPTIONS (3000K | 4000K)

13W 1270lm | 1320lm **10W** 1105lm | 1150lm **8W** 960lm | 1000lm

BEAM OPTIONS

60° **STANDARD** 36° 24° 15°

FINISHES

☐ WHITE ☒ BLACK

GENERAL SPECIFICATIONS

EFFICACY Up to 95 Lm/W
COLOUR 3000K, Warm White
4000K, Cool White
MATERIAL Powder Coated Aluminium
CRI 92+
IP 44
COLOUR DEVIATION SDCM ≤2
UGR <19
LIFETIME > 55,000hrs L80B10
WARRANTY 7 Years

DRIVER SPECIFICATIONS

DIMENSIONS L 104 x W 43 x H 24mm
POWER 350mA | 300mA | 250mA
240V Remote Flicker Free
Dimmable Driver
DIMMING Phase Cut Dimming
POWER FACTOR > 0.90

PROJECT DETAILS

PROJECT

TYPE

NOTES

PRODUCT CODES

White, 3000K, 60° **118-ED2L13W603**
White, 4000K, 60° **118-ED2L13W604**
Black, 3000K, 60° **118-ED2L13B603**
Black, 4000K, 60° **118-ED2L13B604**

ACCESSORIES

36° Reflector **118-RFLP36**
24° Reflector **118-RFLP24**
15° Reflector **118-RFLP15**

DRIVER CODES

DRIVER SOLD SEPERATELY

13W **118-350MA**
10W **118-300MA**
8W **118-250MA**

DALI DIMMING AVAILABLE UPON REQUEST

