



FLOW PLUS TOP STRAIGHT ENTRY

Flow Plus LED strip is the best of its class. Constructed from polyurethane, it features an IP rating of 68, is offered in three different lengths and 2 different wattages. Flow Top is perfect for designs that require a direct application or a vertical bend.

- Top emitting LED – For applications requiring direct light.
- UV & chemical resistant.
- 5W & 10W options available in either 1m, 3m, or 5m rolls.
- Custom lengths available upon request. (Minimum order quantity).
- IP 68 – Suitable outdoors & wet areas.
- Dimmable – Determined by driver.



DIMENSIONS

W 16 mm

H 15 mm

LUMINAIRE OPTIONS

LED & LUMENS OPTIONS (3000K & 4000K)

5W PER METER
330 lm

10W PER METER
636lm

GENERAL SPECIFICATIONS

LED 24V DC 5W p/m 10W p/m

LUMENS (3000K & 4000K) 330 636

EFFICACY P/METER 66 lm/w 64 lm/w

COLOUR 3000K, Warm White
4000K, Cool White

MATERIAL Extruded Silicone

FINISH White

BEAM 120°

CRI 92+

IP 68

COLOUR DEVIATION SDCM ≤ 2

BENDING DIAMETER 300mm

LIFETIME > 54,000hrs L80B10

WARRANTY 5 Years

LENGTHS AVAILABLE 1m | 3m | 5m
Custom lengths are available with a minimum order request.

COMPATIBLE CASAMBI DEVICES

BasicDIM 24V Wireless 4ch **71-CAS24V**

BasicDIM Driver 24V 150W **71-CAS24V150**

BasicDIM Driver 24V 100W **71-CAS24V100**

BasicDIM Driver 24V 60W **71-CAS24V60**

BasicDIM Driver 24V 35W **71-CAS24V35**

PROJECT DETAILS

PROJECT

TYPE

NOTES

PRODUCT CODES

5W

3000K, 1m **10-FPTF0531**
3000K, 3m **10-FPTF0533**
3000K, 5m **10-FPTF0535**
4000K, 1m **10-FPTF0541**
4000K, 3m **10-FPTF0543**
4000K, 5m **10-FPTF0545**

10W

3000K, 1m **10-FPTF1031**
3000K, 3m **10-FPTF1033**
3000K, 5m **10-FPTF1035**
4000K, 1m **10-FPTF1041**
4000K, 3m **10-FPTF1043**
4000K, 5m **10-FPTF1045**

ACCESSORY

ALUMINIUM PROFILE

MATERIAL Aluminium

PRODUCT CODE 10-FP1615P1

DIMENSIONS 1000 (L) x 18.6 (W)
x 17.8 (H) mm

