

SPLIT

Designed to revolve around any application, the Split ceiling light is minimalist in design and precise in lighting distribution. Highly adaptable, this luminaire is an ideal lighting solution when paired together or used individually, for both residential and commercial applications.

- Innovating rotating lens head.
- High quality aluminium housing.
- Light any surface – Adjustable up to 60°, with 350° rotation.
- Discreet lock-in mount, complimenting its minimalist design.



DIMENSIONS **W** Ø65mm **H** 200mm

LUMINAIRE OPTIONS

BEAM OPTIONS

50° **STANDARD** 36° 25°

FINISHES

☐ WHITE ☒ BLACK

BAFFLE FINISHES

☐ WHITE ☒ BLACK ☐ GOLD

LENS OPTION

☐ CLEAR **STANDARD** ☒ HONEYCOMB

GENERAL SPECIFICATIONS

LED **LUMENS** (3000K | 4000K)

12W 1085 lm | 1195 lm

EFFICACY Up to 99 Lm/W

COLOUR 3000K, Warm White
4000K, Cool White

MATERIAL Powder Coated Material

CRI 90+

IP 20

COLOUR DEVIATION SDCM ≤3

UGR <19

LIFETIME > 55,000hrs L80B10

WARRANTY 5 Years

DRIVER SPECIFICATIONS

POWER 350mA 240V
Built-In Driver

DIMMING Phase Cut Dimming

POWER FACTOR > 0.90

REMOTE DALI DIMMING AVAILABLE UPON REQUEST

PROJECT DETAILS

PROJECT

TYPE

NOTES

PRODUCT CODES

White, 3000K, 50° **83-SP12W503**

White, 4000K, 50° **83-SP12W504**

Black, 3000K, 50° **83-SP12B503**

Black, 4000K, 50° **83-SP12B504**

ACCESSORIES

36° Reflector **83-RFL36**

24° Reflector **83-RFL25**

Honeycomb Lens **83-AIRH**

White Baffle **83-SPLITRW**

Black Baffle **83-SPLITRB**

Gold Baffle **83-SPLITRG**

