

SPLIT TRACK

Highly adaptable, the SPLIT TRACK is the perfect design solution. Paired together or used individually, the Split Track has a modern design aesthetic that fits seamlessly into any interior space.

- Innovating rotating lens head.
- High quality aluminium housing.
- Light any surface – Adjustable up to 60°, with 350° rotation.
- Discreet lock-in mount, complimenting its minimalist design.



DIMENSIONS W Ø65mm H 200mm

LUMINAIRE OPTIONS

BEAM OPTIONS

50° **STANDARD** 36° 25°

FINISHES

☐ WHITE ☒ BLACK

BAFFLE FINISHES

☐ WHITE ☒ BLACK ☐ GOLD

LENS OPTION

☐ CLEAR **STANDARD** ☒ HONEYCOMB

GENERAL SPECIFICATIONS

LED LUMENS (3000K | 4000K)

12W 1255 lm | 1320 lm

EFFICACY Up to 110 Lm/W

COLOUR 3000K, Warm White
4000K, Cool White

MATERIAL Powder Coated Material

CRI 90+

IP 20

COLOUR DEVIATION SDCM ≤3

UGR <19

LIFETIME > 55,000hrs L80B10

WARRANTY 5 Years

DRIVER SPECIFICATIONS

POWER 350mA 240V
Built-In Driver

DIMMING Phase Cut Dimming

POWER FACTOR > 0.90

REMOTE DALI DIMMING AVAILABLE UPON REQUEST

PROJECT DETAILS

PROJECT

TYPE

NOTES

PRODUCT CODES

White, 3000K, 50° **83-SPT12W503**

White, 4000K, 50° **83-SPT12W504**

Black, 3000K, 50° **83-SPT12B503**

Black, 4000K, 50° **83-SPT12B504**

ACCESSORIES

36° Reflector **83-RFL36**

24° Reflector **83-RFL25**

Honeycomb Lens **83-AIRH**

White Baffle **83-SPLITRW**



Black Baffle **83-SPLITRB**

Gold Baffle **83-SPLITRG**



3 CIRCUIT TRACK COMPONENTS

3 Circuit Track Piece



DESCRIPTION

3 circuit track, available in 1m or 2m lengths.

H 32.5mm W 31.5mm



FINISHES

- 1m, White
- 1m, Black
- 2m, White
- 2m, Black

PRODUCT CODE

- 83-3C1MW
- 83-3C1MB
- 83-3C2MW
- 83-3C2MB

3 Circuit Recessed Track Piece




3 circuit recessed track, available in 1m or 2m lengths.

H 32.5mm W1 31.5mm W2 56mm

- 1m, White
- 1m, Black
- 2m, White
- 2m, Black

- 83-3CR1MW
- 83-3CR1MB
- 83-3CR2MW
- 83-3CR2MB

Feed Piece



The feed piece connects at the start of the track and supplies power to the entire track configuration.

W1 66mm W2 105mm

- White
- Black

- 83-3CFPW
- 83-3CFPB

Dead End




The dead end connects at the end of the track and completes the track with a clean finish.

W1 3mm W2 21mm

- White
- Black

- 83-3CDEW
- 83-3CDEB

Straight Connector




The straight connector joins two separate pieces of track together.

W 68mm

- White
- Black

- 83-3CSCW
- 83-3CSCB

Straight Connector Feed



The straight connector feed connects in the middle of two track pieces and supplies power to the entire track configuration. You can use a straight connector feed instead of a regular feed piece.

W1 100mm W2 166mm













- White
- Black

- 83-3CSFW
- 83-3CSFB

Please Note:

3 circuit recessed track is configured using the same components as the standard 3 circuit track. However in addition to this, cover plates are required. Please get in touch with one of our design consultants for more information.

3 CIRCUIT TRACK COMPONENTS

Corner Connector		DESCRIPTION	FINISHES	PRODUCT CODE
		<p>The corner connector is used to connect two pieces of track in a corner configuration. These pieces are available in both right and left configurations. A corner connector can also provide power to the track.</p> <p>H2 W 99mm H1 66mm</p>	<div> <div></div> Left, White <div></div> Left, Black <div></div> Right, White <div></div> Right, Black </div>	83-3CLCW 83-3CLCB 83-3CRCW 83-3CRCB
T Connector		DESCRIPTION	FINISHES	PRODUCT CODE
		<p>The T Connector is used to connect three pieces of track in a T configuration. The T Connector can also supply power to the track. Available in left and right configurations.</p> <p>H1 66mm H2 99mm W1 100mm W2 166mm</p>	<div> <div></div> Left, White <div></div> Left, Black <div></div> Right, White <div></div> Right, Black </div>	83-3CTLCW 83-3CTLCB 83-3CTRCW 83-3CTRCB
Cross Connector		DESCRIPTION	FINISHES	PRODUCT CODE
		<p>The cross connector is used to connect four pieces of track in a cross configuration. The cross connector also supplies power to the track.</p> <p>H1 100mm H2 166mm W1 100mm W2 166mm</p>	<div> <div></div> White <div></div> Black </div>	83-3CCCCW 83-3CCCCB
Adaptor		DESCRIPTION	FINISHES	PRODUCT CODE
		<p>The adaptor is a clip-in component which comes as standard on every FAZE track fitting. The adaptor is used to connect the luminaire to the track.</p> <p>The adaptor can carry fittings of 5kg or less.</p> <p>H 39mm W 30mm</p>	<div> <div></div> White <div></div> Black </div>	83-3CCCCW 83-3CCCCB
Wire Suspension Kit		DESCRIPTION	FINISHES	PRODUCT CODE
		<p>The wire suspension kit is used to suspend the track configuration.</p>	<div> <div></div> White <div></div> Black <div></div> Silver </div>	83-3CWSUPW 83-3CWSUPB 83-3CWSUP
Universal Fixing Piece		DESCRIPTION	FINISHES	PRODUCT CODE
		<p>The universal fixing piece can be used to mount the track in a fixed position.</p>	<div> <div></div> White <div></div> Black </div>	83-3CUFW 83-3CUFB

Please Note:

3 circuit recessed track is configured using the same components as the standard 3 circuit track. However in addition to this, cover plates are required. Please get in touch with one of our design consultants for more information.