TWIST

A stylish feature to incorporate into any space, providing seamless light in any direction, with a 360° revolving hinge, and up to 90° rotation.

- High CRI –Defining architectural details and finishes.
- Quick connection system For durability and easy installation.
- Perfect light application Available in 4 beam angles. •
- High quality lens For superior light emission.
- Available as surface mounted or recessed.

PROJECT

TYPE

NOTES

| Image: Constraint of the second o |
|---|
| CELLING MOUNT I 150mm ILUMINAIRE OPTIONS MOUNTING OPTIONS SURFACE RECESSED White, 3000K, 60° 7-TWIS13W503 White, 4000K, 60° 7-TWIS13W504 Black, 3000K, 60° 7-TWIS13B50 Black, 4000K, 60° FINISHES WHITE BLACK |
| LUMINAIRE OPTIONS PRODUCT CODES MOUNTING OPTIONS White, 3000K, 60° 7-TWIS13W503 SURFACE RECESSED White, 4000K, 60° 7-TWIS13W504 BEAM OPTIONS Black, 3000K, 60° 7-TWIS13B50 50° STANDARD 36° 25° 15° FINISHES HITE BLACK ACCESSORIES |
| MOUNTING OPTIONS White, 3000K, 60° 7-TWIS13W503 SURFACE RECESSED White, 4000K, 60° 7-TWIS13W504 BEAM OPTIONS Black, 3000K, 60° 7-TWIS13B50 50° STANDARD 36° 25° 15° FINISHES Black, 4000K, 60° 7-TWIS13B503 WHITE BLACK ACCESSORIES |
| SURFACE RECESSED White, 4000K, 60° 7-TWIS13W504 BEAM OPTIONS Black, 3000K, 60° 7-TWIS13B50 50° STANDARD 36° 25° FINISHES Black 4000K, 60° 7-TWIS13B503 |
| BEAM OPTIONS Black, 3000K, 60° 7-TWIS13B50 50° STANDARD 36° 25° 15° FINISHES Black 4000K, 60° 7-TWIS13B503 WHITE BLACK ACCESSORIES |
| 50° STANDARD 36° 25° 15° Black, 4000K, 60° 7-TWIS13B503 FINISHES |
| FINISHES WHITE BLACK ACCESSORIES |
| WHITE BLACK ACCESSORIES |
| |
| BAFFLE FINISHES Ceiling Mount Kit, White 7-TWISCMKW |
| |
| WHITE BLACK Ceiling Mount Kit, Black 7-TWISCMKB |
| Recessed Mount Kit, White 7-TWISRMKW |
| GENERAL SPECIFICATIONS Recessed Mount Kit, Black 7-TWISRMKB |
| LED LUMENS (3000K 4000K) 36° Lens 7-TWISLNS36 |
| 13W 1400 lm 1500 lm 25° Lens 7-TWISLNS25 |
| EFFICACY Up to 115 Lm/W 15° Lens 7-TWISLNS15 |
| COLOUR 3000K, Warm White 4000K, Cool White 7-TWISH |
| Gold Baffle 7-TWISGB |
| MATERIAL Powder Coated Aluminium White Baffle 7-TWISWB CRI 90+ |
| |
| $ \begin{array}{c} \mathbf{P} \\ \mathbf{Colour Deviation} \\ \mathbf{SDCM} \leq 3 \end{array} $ |
| |
| LIFETIME > 55,000hrs L80B10 |
| WARRANTY 5 Years |
| DRIVER SPECIFICATIONS |



POWER

DIMMING

POWER FACTOR

350mA 240V Built-In Driver

> 0.95

Phase Cut Dimming