

MODUX 2 & 4 POND

By LuxR

OUTDOOR

Modux 2 & 4 Pond luminaires are mid-size spotlights with a swivel bracket that provides 90 degrees elevation adjustment. The Pondlight has a weighted base and is designed to be installed underwater.

Ø41 (1 ⁵/ଃ")	
	(4 ³ / ₈ ")
	7] [1] [7]
Ø2 (1/2")	



GENERAL SPECIFICATIONS

LED	2 W 4 W	
LUMENS	170 Lm 360 Lm	
EFFICACY	85 Lm / W 90 Lm / W	
COLOUR TEMPERATURE	2700K 3000K 4000K	
MATERIAL	Natural Copper 316 Stainless Steel Powder Coated Aluminium	
FINISH	Copper, Stainless Steel, Black	
BEAM	74°	
CRI	90+	
IP	68	
WARRANTY	10 Years: Copper & Stainless Steel 5 Years: Aluminium & Electronics	
ORIGIN	New Zealand	

POWER SPECIFICATIONS


DRIVER	SERIES WIRING	700mA Constant Current (Remote)
DRIVER	PARALLEL WIRING	12VAC (Integral) Remote 12V Transformer Required
		24VDC (Integral) Remote 24V Driver Required

PRODUCT CODES

PARALLEL WIRING AVAILABLE UPON REQUEST			
M4 STAINLESS STEEL	128-M4SPRS7430WB		
M4 COPPER	128-M4SPRC7430WB		
M4 BLACK	128-M4SPRABK7430WB		
M2 STAINLESS STEEL	128-M2SPRS7430WB		
M2 COPPER	128-M2SPRC7430WB		
M2 BLACK	128-M2SPRABK7430WB		

SERIES WIRING

INPUT 240VAC	OUTPUT DC Constant Current



PARALLEL WIRING

INPUT 240VAC OUTPUT 12VAC | 24VDC

PERTH +61 08 9240 1008 sales@radiantlighting.com.au SYDNEY 1300 438 609 sales@radiantlighting.com.au MELBOURNE 1300 438 609 sales@radiantlighting.com.au BRISBANE 1300 438 609 sales@radiantlighting.com.au

_		
)R	TYPE	

NOTES

PROJECT