

MODUX 2 & 4 LARGE RECESSED ROUND

By LuxR

OUTDOOR

A larger version of the M2 / M4 Recessed Round. The Modux 2 & 4 Large recessed luminaires are designed to be mounted either in the ground or floor as low profile uplighters, or in walls or steps to illuminate paths and stairways. They can be installed either outdoors or indoors and offer the option of either a round or square flange.

NOTES

TYPE

PROJECT

Ø75 (2⁴/4")




GENERAL SPECIFICATIONS

LED	2 W 4 W
LUMENS	170 Lm 360 Lm
EFFICACY	85 Lm / W 90 Lm / W
COLOUR TEMPERATURE	2700K 3000K 4000K
MATERIAL	Natural Copper 316 Stainless Steel Powder Coated Material
FINISH	Black, Copper, Stainless Steel
BEAM MODUX 2 MODUX 4	8°, 26°, 36°, 74°, 15°+40° Oval 12°, 26°, 36°, 74°, 15°+40° Oval
CRI	90+
IP	68
WARRANTY	10 Years: Copper & Stainless Steel 5 Years: Electronics & Aluminium
ORIGIN	New Zealand

SERIES WIRING

INPUT 240VAC	OUTPUT	DC Constant Current



POWER SPECIFICATIONS

DRIVER	SERIES WIRING	700mA Constant Current (Remote)
DRIVER	PARALLEL WIRING	12VAC (Integral) Remote 12V Transformer Required
		24VDC (Integral) Remote 24V Driver Required

PRODUCT CODES (SERIES WIRING)

M2 COPPER 128-M2LRRC7430 M2 STAINLESS STEEL 128-M2LRRS7430 M4 BLACK 128-M4LRRABK7430 M4 COPPER 128-M4LRRC7430	PARALLEL WIRING AVAILABLE UPON REQUEST	
M2 COPPER 128-M2LRRC7430 M2 STAINLESS STEEL 128-M2LRRS7430 M4 BLACK 128-M4LRRABK7430	M4 STAINLESS STEEL	128-M4LRRS7430
M2 COPPER128-M2LRRC7430M2 STAINLESS STEEL128-M2LRRS7430	M4 COPPER	128-M4LRRC7430
M2 COPPER 128-M2LRRC7430	M4 BLACK	128-M4LRRABK7430
	M2 STAINLESS STEEL	128-M2LRRS7430
M2 BLACK 128-M2LRRABK7430	M2 COPPER	128-M2LRRC7430
	M2 BLACK	128-M2LRRABK7430

PARALLEL WIRING

INPUT 240VAC	OUTPUT 12VAC 24VDC
₽	

PERTH +61 08 9240 1008 sales@radiantlighting.com.au SYDNEY 1300 438 609 sales@radiantlighting.com.au MELBOURNE 1300 438 609 sales@radiantlighting.com.au BRISBANE 1300 438 609 sales@radiantlighting.com.au