



radiantlighting®

M2 & M4 LARGE RECESSED SQUARE

By LuxR


OUTDOOR

The Modux 2 & 4 Large recessed luminaires are designed to be mounted either in the ground or floor as low profile uplighters, or in walls or steps to illuminate paths and stairways. They can be installed either outdoors or indoors and offer the option of either a round or square flange.

PROJECT

TYPE

NOTES



GENERAL SPECIFICATIONS

LED	2 W 4 W
LUMENS	170 Lm 360 Lm
EFFICACY	85 Lm / W 90 Lm / W
COLOUR TEMPERATURE	2700K 3000K 4000K
MATERIAL	Natural Copper 316 Stainless Steel Powder Coated Aluminium
FINISH	Black, Copper, Stainless Steel
BEAM MODUX 2 MODUX 4	8°, 26°, 36°, 74°, 15°+40° Oval 12°, 26°, 36°, 74°, 15°+40° Oval
CRI	90+
IP	68
WARRANTY	10 Years: Copper & Stainless Steel 5 Years: Electronics & Aluminium
ORIGIN	New Zealand

POWER SPECIFICATIONS

DRIVER SERIES WIRING	700mA Constant Current (Remote)
DRIVER PARALLEL WIRING	12VAC (Integral) Remote 12V Transformer Required 24VDC (Integral) Remote 24V Driver Required


PRODUCT CODES (SERIES WIRING)

M2 BLACK	128-M2LSRABK7430
M2 COPPER	128-M2LSRC7430
M2 STAINLESS STEEL	128-M2LSRS7430
M4 BLACK	128-M4LSRABK7430
M4 COPPER	128-M4LSRC7430
M4 STAINLESS STEEL	128-M4LSRS7430

PARALLEL WIRING AVAILABLE UPON REQUEST

SERIES WIRING

INPUT 240VAC OUTPUT DC Constant Current



PARALLEL WIRING

INPUT 240VAC OUTPUT 12VAC | 24VDC

