

MODUX 2 & 4 SQUARELIGHT WASH

By LuxR

OUTDOOR

The M2 & M4 Squarelight Wash are a low-voltage dimmable outdoor feature light that produces a wash distribution 5 degrees below the flange lip in a narrow decorative band. Can be used to illuminate the wall surface adjacent to the step treads, step treads themselves, above a doorway, or as a path light wayfinder among other applications. TYPE NOTES

PROJECT

GENERAL SPECIFICATIONS

LED	2 W 4 W		
LUMENS	170 Lm 360 Lm		
EFFICACY	85 Lm / W 90 Lm / W		
COLOUR TEMPERATURE	2700К 3000К 4000К		
MATERIAL	Natural Copper 316 Stainless Steel Powder Coated Aluminium		
FINISH	Black, Copper, Stainless Steel		
BEAM	-5°, +10°		
CRI	90+		
IP	68		
WARRANTY	10 Years: Copper & Stainless Steel 5 Years: Electronics & Aluminium		
ORIGIN	New Zealand		

POWER SPECIFICATIONS


DRIVER SERIES WIRING	700mA Constant Current (Remote)
DRIVER PARALLEL WIRING	12VAC (Integral) Remote 12V Transformer Required
	24VDC (Integral) Remote 24V Driver Required


PRODUCT CODES (SERIES WIRING)

M2 1 FACET WASH		M2 2 FACET WASH		
BLACK	128-M2SQ1RABK30	BLACK	128-M2SQ2RABK30	
COPPER	128-M2SQ1RC30	COPPER	128-M2SQ2RC30	
STAINLESS STEEL	128-M2SQ1RS30	STAINLESS STEEL	128-M2SQ2RS30	
M4 1 FACET WASH		M4 2 FACET WASH		
BLACK	128-M4SQ1RABK30	BLACK	128-M4SQ2RABK30	
COPPER	128-M4SQ1RC30	COPPER	128-M4SQ2RC30	
STAINLESS STEEL	128-M4SQ1RS30	STAINLESS STEEL	128-M4SQ2RS30	
PARALLEL WIRING AVAILABLE UPON REQUEST				

SERIES WIRING

OUTPUT DC Constant Current		





PERTH +61 08 9240 1008 sales@radiantlighting.com.au SYDNEY 1300 438 609 sales@radiantlighting.com.au MELBOURNE 1300 438 609 sales@radiantlighting.com.au

PARALLEL WIRING

BRISBANE 1300 438 609 sales@radiantlighting.com.au