



radiantlighting®

KOI 110 POST

By LOMBARDO

OUTDOOR

Suitable for indoor and outdoor use. Integrated driver 220-240V and the latest generation of LED. Body and cover made of die-cast aluminium primary alloy; highly resistant to oxidization thanks to the zirconium-based passivation treatment and UV stabilized polyester resin coating. Tempered glass diffuser with frosted effect. Silicone gaskets.

PROJECT

TYPE

NOTES



H600



H400

GENERAL SPECIFICATIONS

LED	6 W
LUMENS	375 Lm
EFFICACY	63 Lm / W
COLOUR TEMPERATURE	2700K / 3000K / 4000K
MATERIAL	Aluminium
FINISH	White, Grey, Grey Anthracite, Corten
CRI	80+
IP	66
IK RATING	10
WARRANTY	3 Years
ORIGIN	Italy

POWER SPECIFICATIONS

DRIVER	Integrated, 220-240V
DIMMING	N/A
VOLTAGE	AC Direct, 220-240V

PRODUCT CODES

H600	
WHITE, 3000K	48-LL1210123
GREY, 3000K	48-LL1210133
GREY ANTHRACITE, 3000K	48-LL1210143
CORTEN, 3000K	48-LL1210153
H400	
WHITE, 3000K	48-LL1210163
GREY, 3000K	48-LL1210173
GREY ANTHRACITE, 3000K	48-LL1210183
CORTEN, 3000K	48-LL1210193

2700K & 4000K CODES ARE AVAILABLE UPON REQUEST