



radiantlighting®

KOI 220

By LOMBARDO


WALL

Suitable for indoor and outdoor use. Integrated driver 220-240V and the latest generation of Led. Body and cover made of EN-AB46100 die-cast aluminium primary alloy; highly resistant to oxidization thanks to the zirconium-based passivation treatment and UV stabilized polyester resin coating. Tempered glass diffuser with frosted effect. Silicone gaskets.

PROJECT

TYPE

NOTES



GENERAL SPECIFICATIONS

LED	10 W
LUMENS	650 Lm
EFFICACY	65 Lm / W
COLOUR TEMPERATURE	2700K / 3000K / 4000K
MATERIAL	Aluminium
FINISH	White, Grey, Dark Grey, Black, Corten, Sand
BEAM	N/A
IP	66
CRI	80
IK	10 20J xx9
WARRANTY	3 Years
ORIGIN	Italy

POWER SPECIFICATIONS

DRIVER	Integrated Power Supply
LED	220-240 V

PRODUCT CODES

WHITE, 3000K	48-LL1210083
GREY, 3000K	48-LL1210093
DARK GREY, 3000K	48-LL1210103
WHITE, 4000K	48-LL121008N
GREY, 4000K	48-LL121009N
DARK GREY, 4000K	48-LL121010N