



radiantlighting®

## NOA 50 WALL

By LOMBARDO


WALL

Suitable for outdoor use. Possibility of wall, floor and ceiling installation. Die-cast aluminum body and stem; high resistance to oxidation thanks to cataphoresis treatment and UV-stabilized polyester resin coating. Aluminum reflector. Silicone gaskets to maintain the IP 66 degree. 90° inclination adjustment and 360° rotation. Phase cut dimmable.

### PROJECT

TYPE

NOTES



### GENERAL SPECIFICATIONS

|                    |                                       |
|--------------------|---------------------------------------|
| LED                | 9 W                                   |
| LUMENS             | 1000 Lm                               |
| EFFICACY           | 111 Lm / W                            |
| COLOUR TEMPERATURE | 2700K, 3000K, 4000K                   |
| MATERIAL           | Die-Cast Aluminium                    |
| FINISH             | White, Grey, Anthracite, Brown, Green |
| IP                 | 66                                    |
| BEAM               | 60° / 40° / 20°                       |
| CRI                | 80                                    |
| WARRANTY           | 5 Years                               |
| ORIGIN             | Italy                                 |

### POWER SPECIFICATIONS

|          |                    |
|----------|--------------------|
| DRIVER   | Integrated         |
| VOLTAGE  | AC DIRECT 220-240V |
| DIMMABLE | Phase Cut          |

### PRODUCT CODES

|                   |              |
|-------------------|--------------|
| WHITE, 3000K      | 48-LL1330203 |
| GREY, 3000K       | 48-LL1330213 |
| ANTHRACITE, 3000K | 48-LL1330223 |
| BROWN, 3000K      | 48-LL1330233 |
| GREEN, 3000K      | 48-LL1330243 |
| WHITE, 4000K      | 48-LL133020N |
| GREY, 4000K       | 48-LL133021N |
| ANTHRACITE, 4000K | 48-LL133022N |
| BROWN, 4000K      | 48-LL133023N |
| GREEN, 4000K      | 48-LL133024N |

### ACCESSORY CODES

BEAM ANGLE CODES AVAILABLE UPON REQUEST