

TAPE 220

By LOMBARDO


WALL

Also suitable for outdoor use. Die-cast primary aluminium body EN-AB46100; high resistance to oxidation thanks to cataphoresis treatment and painting with polyester resins stabilised against UV rays. Satin-finish toughened glass diffuser. Wall or standard box fixing bracket in AISI 316L steel. Power supply 24V, ballast not included.

PROJECT

TYPE

NOTES



GENERAL SPECIFICATIONS

LED	4.6 W
LUMENS	550 Lm
EFFICACY	119 Lm / W
COLOUR TEMPERATURE	2700K / 3000K / 4000K
MATERIAL	Aluminium
FINISH	White, Grey, Dark Grey, Black, Gold, Corten, Sand
BEAM	N/A
IP	66
CRI	80
IK	06 1J xx3
WARRANTY	3 Years
ORIGIN	Italy

POWER SPECIFICATIONS

DRIVER	Integrated Power Supply
LED	AC DIRECT

PRODUCT CODES

WHITE, 3000K	48-LL14503W3
GREY, 3000K	48-LL14503L3
DARK GREY, 3000K	48-LL14503D3
CORTEN, 3000K	48-LL14503K3
GOLD, 3000K	48-LL14503Z3
WHITE, 4000K	48-LL14503WN
GREY, 4000K	48-LL14503LN
DARK GREY, 4000K	48-LL14503DN
CORTEN, 4000K	48-LL14503KN
GOLD, 4000K	48-LL14503ZN