

# **FLOW PLUS SIDE REAR ENTRY**



Our brand new FAZE FLOW PLUS SIDE is a high quality, flexible polyurethane strip. It is ideal for use along ceilings, walls, cabinetry and stairways; both indoors and outdoors. This strip will ensure a seamless combination of style and functionality to any project!

### **FEATURES**

- + Side emitting, for curving around surfaces where you require indirect light
- + UV & chemical resistant
- + 5W or 10W options available, in either 1m, 3m or 5m rolls
- + Compatible with Casambi devices
- + IP68 Waterproof
- + Dimmable (determined by driver)
- + Custom lengths available upon request (minimum order quantity applies)





























### **GENERAL SPECIFICATIONS**

LED	5W p/m   10W p/m <b>(24V DC)</b>	
Lumens	<b>5W p/m -</b> 264 lm p/m (3000K & 4000K) <b>10W p/m</b> - 528 lm p/m (3000K & 4000K)	
Efficacy	<b>5W p/m</b> - 52 lm/w (3000K & 4000K) <b>10W p/m</b> - 52 lm/w (3000K & 4000K)	
Colour Temperature	3000K, Warm White 4000K, Cool White	
Material	Polyurethane	
Finish	White	
Beam	120°	
CRI	92+	
IP	68	
Colour Deviation	SDCM ≤2	
Lifetime	>54,000hrs L70 B10	
Warranty	5 Years	

## **COMPATIBLE CASAMBI DEVICES**


BasicDIM 24V Wireless 4ch	71-CAS24V
BasicDIM Driver 24V 150W	71-CAS24V150
BasicDIM Driver 24V 100W	71-CAS24V100
BasicDIM Driver 24V 60W	71-CAS24V60
BasicDIM Driver 24V 35W	71-CAS24V35

#### **PROJECT DETAILS**

PROJECT:		
TYPE:		

NOTES:


## **DIMENSIONS (mm)**



PRC	DUCI	COD	<b>ES</b>
 _			40

5W, 3000K, 1m	10-FPSR0531
5W, 3000K, 3m	10-FPSR0533
5W, 3000K, 5m	10-FPSR0535
5W, 4000K, 1m	10-FPSR0541
5W, 4000K, 3m	10-FPSR0543
5W, 4000K, 5m	10-FPSR0545
10W, 3000K, 1m	10-FPSR1031
10W, 3000K, 3m	10-FPSR1033
10W, 3000K, 5m	10-FPSR1035
10W, 4000K, 1m	10-FPSR1041
10W, 4000K, 3m	10-FPSR1043
10W, 3000K, 5m	10-FPSR1045

## **ACCESSORIES**



**ALUMINIUM PROFILE** 

**Dimensions:**1000 (L) x 14.4 (W)

x 21.4 (H) mm Material: Aluminium

Product Code: 10-FP1220P1

FRONT VIEW

