

FLOW PLUS SIDE REAR ENTRY



Our brand new FAZE FLOW PLUS SIDE is a high quality, flexible polyurethane strip. It is ideal for use along ceilings, walls, cabinetry and stairways; both indoors and outdoors. This strip will ensure a seamless combination of style and functionality to any project!

FEATURES

- + Side emitting, for curving around surfaces where you require indirect light
- + UV & chemical resistant
- + 5W or 10W options available, in either 1m, 3m or 5m rolls
- + Compatible with Casambi devices
- + IP68 Waterproof
- + Dimmable (determined by driver)
- + Custom lengths available upon request (minimum order quantity applies)





























GENERAL SPECIFICATIONS

LED	5W p/m 10W p/m (24V DC)	
Lumens	5W p/m - 264 lm p/m (3000K & 4000K) 10W p/m - 528 lm p/m (3000K & 4000K)	
Efficacy	5W p/m - 52 lm/w (3000K & 4000K) 10W p/m - 52 lm/w (3000K & 4000K)	
Colour Temperature	3000K, Warm White 4000K, Cool White	
Material	Polyurethane	
Finish	White	
Beam	120°	
CRI	92+	
IP	68	
Colour Deviation	SDCM ≤2	
Lifetime	>54,000hrs L70 B10	
Warranty	5 Years	

COMPATIBLE CASAMBI DEVICES


BasicDIM 24V Wireless 4ch	71-CAS24V
DasicDilvi 24V VVII eless 4cm	7 I-CR324V
BasicDIM Driver 24V 150W	71-CAS24V150
BasicDIM Driver 24V 100W	71-CAS24V100
BasicDIM Driver 24V 60W	71-CAS24V60
BasicDIM Driver 24V 35W	71-CAS24V35

PROJECT DETAILS

PROJECT:		
TYPE:		

NOTES:

DIMENSIONS (mm)



PRODUCT CODES			
5W, 3000K, 1m	10-FPSR0531		
5W, 3000K, 3m	10-FPSR0533		
5W, 3000K, 5m	10-FPSR0535		
5W, 4000K, 1m	10-FPSR0541		
5W, 4000K, 3m	10-FPSR0543		
5W, 4000K, 5m	10-FPSR0545		
10W, 3000K, 1m	10-FPSR1031		
10W, 3000K, 3m	10-FPSR1033		
10W, 3000K, 5m	10-FPSR1035		
10W, 4000K, 1m	10-FPSR1041		
10W, 4000K, 3m	10-FPSR1043		
10W, 3000K, 5m	10-FPSR1045		

ACCESSORIES

10-FP1220P1 Aluminium Profile 1000 (L) x 14.4 (W) x 21.4 (H) mm 10-FP1220MC Aluminium Mounting Clips (set of 2)

