



LINE OPAL RECESSED



The LINE OPAL RECESSED is suitable across both residential and commercial projects. If the four different lengths are not enough, you can connect them together and create your own.

FEATURES

- + Recessed design providing simplicity and functionality
- + Quick and easy connection system
- + Easy installation into ceiling with spring clips attached to fitting
- + Compatible with remote Casambi CBU-TED Bluetooth Controllable Dimmer (71-CASCBU)



GENERAL SPECIFICATIONS

LED	15W 30W 45W 60W
Lumens	1200 lm 2300 lm 3900 lm 4600 lm (3000K) 1230 lm 2424 lm 3955 lm 4850 lm (4000K)
Efficacy	80 lm/w 76 lm/w 86 lm/w 76 lm/w (3000K) 82 lm/w 81 lm/w 88 lm/w 81 lm/w (3000K)
Colour Temperature	 3000K, Warm White  4000K, Cool White
Material	Powder Coated Aluminium
Finish	White Black
Beam	90°
CRI	90+
IP	40
Colour Deviation	SDCM ≤3
UGR	<21
Lifetime	>100,000hrs L80 B10
Warranty	5 Years

ACCESSORY CODES

Recessed Connection Kit	7-LR56CONNECT
-------------------------	---------------

PROJECT DETAILS

PROJECT:

TYPE:

NOTES:

DIMENSIONS (mm)



DRIVER SPECIFICATIONS

L 105 x W 43 x H 24 mm

240V Remote Flicker Free Driver

15W 300mA | 30W 600mA

45W 900mA | 60W 1200mA

Dimming	Phase Cut Dimming
Power Factor	>0.90

PRODUCT CODES

613mm, 15W, White, 3000K	7-LR560615W903
613mm, 15W, White, 4000K	7-LR560615W904
613mm, 15W, Black, 3000K	7-LR560615B903
613mm, 15W, Black, 4000K	7-LR560615B904
1213mm, 30W, White, 3000K	7-LR561230W903
1213mm, 30W, White, 4000K	7-LR561230W904
1213mm, 30W, Black, 3000K	7-LR561230B903
1213mm, 30W, Black, 4000K	7-LR561230B904
1813mm, 45W, White, 3000K	7-LR561845W903
1813mm, 45W, White, 4000K	7-LR561845W904
1813mm, 45W, Black, 3000K	7-LR561845B903
1813mm, 45W, Black, 4000K	7-LR561845B904
2413mm, 60W, White, 3000K	7-LR562460W903
2413mm, 60W, White, 4000K	7-LR562460W904
2413mm, 60W, Black, 3000K	7-LR562460B903
2413mm, 60W, Black, 4000K	7-LR562460B904

