



The LINE OPAL RECESSED is suitable across both residential and commercial projects. If the four different lengths are not enough, you can connect them together and create your own.

## FEATURES

- + Recessed design providing simplicity and functionality
- + Quick and easy connection system
- + Easy installation into ceiling with spring clips attached to fitting
- + Compatible with remote Casambi CBU-TED Bluetooth Controllable Dimmer (71-CASCBU)



## GENERAL SPECIFICATIONS

|                           |  |
|---------------------------|--|
| <b>LED</b>                | 15W   30W   45W   60W  |
| <b>Lumens</b>             | 1200 lm   2300 lm   3900 lm   4600 lm (3000K)<br>1230 lm   2424 lm   3955 lm   4850 lm (4000K) |
| <b>Efficacy</b>           | 80 lm/w   76 lm/w   86 lm/w   76 lm/w (3000K)<br>82 lm/w   81 lm/w   88 lm/w   81 lm/w (3000K) |
| <b>Colour Temperature</b> | 3000K, Warm White<br>4000K, Cool White   |
| <b>Material</b>           | Powder Coated Aluminium  |
| <b>Finish</b>             | White   Black  |
| <b>Beam</b>               | 90°  |
| <b>CRI</b>                | 90+  |
| <b>IP</b>                 | 40   |
| <b>Colour Deviation</b>   | SDCM ≤3  |
| <b>UGR</b>                | <21  |
| <b>Lifetime</b>           | >60,000hrs L80 B10   |
| <b>Warranty</b>           | 5 Years  |

## ACCESSORY CODES

|                                |               |
|--------------------------------|---------------|
| <b>Recessed Connection Kit</b> | 7-LR56CONNECT |
|--------------------------------|---------------|


## PROJECT DETAILS

PROJECT:

TYPE:

NOTES:

## DIMENSIONS (mm)



⌀ 613mm | 1213mm | 1813mm | 2413mm



⌀ (Including Mounting Clips) 65mm

⌀ 56mm (Without Mounting Clips) 45mm

## DRIVER SPECIFICATIONS

**L 105 x W 43 x H 24 mm**

**240V Remote Flicker Free Driver**

**15W** 300mA | **30W** 600mA

**45W** 900mA | **60W** 1200mA

**Dimming** Phase Cut Dimming

**Power Factor** >0.90

## PRODUCT CODES

|                           |                       |
|---------------------------|-----------------------|
| 613mm, 15W, White, 3000K  | <b>7-LR560615W903</b> |
| 613mm, 15W, White, 4000K  | <b>7-LR560615W904</b> |
| 613mm, 15W, Black, 3000K  | <b>7-LR560615B903</b> |
| 613mm, 15W, Black, 4000K  | <b>7-LR560615B904</b> |
| 1213mm, 30W, White, 3000K | <b>7-LR561230W903</b> |
| 1213mm, 30W, White, 4000K | <b>7-LR561230W904</b> |
| 1213mm, 30W, Black, 3000K | <b>7-LR561230B903</b> |
| 1213mm, 30W, Black, 4000K | <b>7-LR561230B904</b> |
| 1813mm, 45W, White, 3000K | <b>7-LR561845W903</b> |
| 1813mm, 45W, White, 4000K | <b>7-LR561845W904</b> |
| 1813mm, 45W, Black, 3000K | <b>7-LR561845B903</b> |
| 1813mm, 45W, Black, 4000K | <b>7-LR561845B904</b> |
| 2413mm, 60W, White, 3000K | <b>7-LR562460W903</b> |
| 2413mm, 60W, White, 4000K | <b>7-LR562460W904</b> |
| 2413mm, 60W, Black, 3000K | <b>7-LR562460B903</b> |
| 2413mm, 60W, Black, 4000K | <b>7-LR562460B904</b> |