



LINE OPAL



The LINE OPAL is as practical as it is stylish, it can be surface mounted or suspended; providing flexibility across both residential and commercial projects. If the four different lengths are not enough, you can connect them together and create your own.

FEATURES

- + Surface mounted or suspended options
- + Specially designed ceiling canopy for fast installation and seamless design
- + Quick and easy connection system
- + Surface Mount option has 3mm detail from ceiling once installed



GENERAL SPECIFICATIONS

LED	15W 30W 45W 60W
Lumens	1000 lm 2000 lm 3000 lm 4000 lm (3000K)
Colour	<div><div></div> 3000K, Warm White</div> <div><div></div> 4000K, Cool White</div>
Efficacy	Up to 88 lm/w (3000K)
Beam	90°
Material	Aluminium
CRI	90+
Finish	White Black
IP	40
Colour Deviation	SDCM ≤3
Lifetime	L70 >60,000hrs
Warranty	5 Years

ACCESSORIES

Aluminium Joiners	7-LI41CONNECT
Surface Mount Clip	7-LI41CLIP


PROJECT DETAILS

PROJECT:

TYPE:

NOTES:

DIMENSIONS (mm)



DRIVER SPECIFICATIONS

Power	240V Built-In Flicker Free Driver
Dimming	Phase Cut Dimming
Power Factor	> 0.90

PRODUCT CODE

600mm, 15W, White, 3000K	7-LI410615W903
600mm, 15W, White, 4000K	7-LI410615W904
600mm, 15W, Black, 3000K	7-LI410615B903
600mm, 15W, Black, 4000K	7-LI410615B904
1200mm, 30W, White, 3000K	7-LI411230W903
1200mm, 30W, White, 4000K	7-LI411230W904
1200mm, 30W, Black, 3000K	7-LI411230B903
1200mm, 30W, Black, 4000K	7-LI411230B904
1800mm, 45W, White, 3000K	7-LI411845W903
1800mm, 45W, White, 4000K	7-LI411845W904
1800mm, 45W, Black, 3000K	7-LI411845B903
1800mm, 45W, Black, 4000K	7-LI411845B904
2400mm, 60W, White, 3000K	7-LI412460W903
2400mm, 60W, White, 4000K	7-LI412460W904
2400mm, 60W, Black, 3000K	7-LI412460B903
2400mm, 60W, Black, 4000K	7-LI412460B904

