

# **LITE 108**



The high-performance Faze LITE 108 features the latest in LED technology with high lumen per watt efficacy and visually dynamic illumination.

#### **FEATURES**

- + Precision reflector with clear lens for better light distribution and performance
- + Specially designed heat sink for class leading heat dissipation
- + IP 44 Suitable for wet areas
- + Compatible with remote Casambi CBU-TED Bluetooth Controllable Dimmer (71-CASCBU) & with Casambi BasicDim Driver 13W (71-CAS350)



# **GENERAL SPECIFICATIONS LED** 12W 1050 lm (3000K) | 1110 lm (4000K) Lumens 3000K, Warm White Colour 4000K, Cool White 87 lm/w (3000K) | 92 lm/w (4000K) **Efficacy Beam** 36° | 60° **Material** Powder Coated Aluminium CRI 92+ Finish White | Black 44 **Colour Deviation** SDCM ≤2 Lifetime L70 >310,000hrs 5 Years Warranty

 $\textbf{\textit{Please Note:}} \ \ \textbf{When using C-Bus, use universal or trailing edge dimming modules}$ 


#### **PROJECT DETAILS**

PROJECT:

TYPE:

NOTES:

## **DIMENSIONS (mm)**



## **DRIVER SPECIFICATIONS**

### L 104 x W 43 x H 24 mm

Power	240V Remote Driver
Dimming	Phase Cut Dimming
Power Factor	> 0.90

#### DALI dimming available upon request

PRODUCT CODES	
White, 3000K, 60°	118-LI2L12W603
White, 4000K, 60°	118-LI2L12W604
Black, 3000K, 60°	118-LI2L12B603
Black, 4000K, 60°	118-LI2L12B604

### **REFLECTOR CODE**

36° Reflector 118-RFLLL36

