

# **LITE MINI**



The high-performance Faze LITE MINI features the latest in LED technology with high lumen per watt efficacy and visually dynamic illumination.

## **FEATURES**

- + Precision reflector with clear lens for better light distribution and performance
- + Specially designed heat sink for class leading heat dissipation
- + IP 44 Suitable for wet areas
- + IC-4 rated
- + Compatible with remote Casambi CBU-TED Bluetooth Controllable Dimmer (71-CASCBU) & with Casambi BasicDim Driver 11W (71-CAS300)



## **GENERAL SPECIFICATIONS LED** 10W 870 lm (3000K) | 1000 lm (4000K) Lumens 3000K, Warm White Colour 4000K, Cool White 87 lm/w (3000K) | 100 lm/w (4000K) **Efficacy** 36° | 60° **Beam** Powder Coat Aluminium **Material** CRI 92+ **Finish** White | Black IP 44 **Colour Deviation** SDCM ≤2 Lifetime L70 >310,000hrs 5 Years Warranty

**Please Note:** When using C-Bus, use universal or trailing edge dimming modules

#### **PROJECT DETAILS**


PROJECT:		
TYPE:		

NOTES:

## **DIMENSIONS (mm)**

49





### **DRIVER SPECIFICATIONS**

#### L 104 x W 43 x H 24 mm

Power	240V Remote Driver
Dimming	Phase Cut Dimming
Power Factor	> 0.90

PRODUCT CODE			
White, 3000K, 36°	118-LI2M10W363		
White, 3000K, 60°	118-LI2M10W603		
White, 4000K, 36°	118-LI2M10W364		
White, 4000K, 60°	118-LI2M10W604		
Black, 3000K, 36°	118-LI2M10B363		
Black, 3000K, 60°	118-LI2M10B603		
Black, 4000K, 36°	118-LI2M10B364		
Black, 4000K, 60°	118-LI2M10B604		

