

## PROJECT DETAILS

PROJECT:

TYPE:


NOTES:

## FEATURES

- + Minimalist cylinder design, available in various colours and lengths
- + Sophisticated lens technology for enhanced visual comfort
- + Black baffle for reduced glare
- + Seamless canopy with quick connection for easy installation
- + Perfect for both individual use or as a cluster
- + Compatible with remote Casambi CBU-TED Bluetooth Controllable Dimmer (71-CASCBU)



## DIMENSIONS (mm)



## GENERAL SPECIFICATIONS

LED	6W	
Lumens	400 lm (3000K)	
Colour	<input type="checkbox"/> 3000K, Warm White <input type="checkbox"/> 4000K, Cool White	
Efficacy	66.79 lm/w (3000K)	
Beam	60°	
Material	Powder Coated Aluminium	
CRI	92+	
Finish	White   Black	
IP	20	
UGR	<15	
Colour Deviation	SDCM ≤2	
Lifetime	310,000hrs L70B10	
Additional Lens Options	15°	118-SIL4015
	24°	118-SIL4024
	36°	118-SIL4036
	45°	118-SIL4045
Warranty	5 Years	

## DRIVER SPECIFICATIONS

Power	150mA 240V Built-In Flicker Free Dimmable Driver
Dimming	Phase-Cut Dimming
Power Factor	>0.90

*Remote DALI dimming available upon request*

## PRODUCT CODE

280, White, 3000K	118-SIS42806W603
280, White, 4000K	118-SIS42806W604
280, Black, 3000K	118-SIS42806B603
280, Black, 4000K	118-SIS42806B604
380, White, 3000K	118-SIS43806W603
380, White, 4000K	118-SIS43806W604
380, Black, 3000K	118-SIS43806B603
380, Black, 4000K	118-SIS43806B604
580, White, 3000K	118-SIS45806W603
580, White, 4000K	118-SIS45806W604
580, Black, 3000K	118-SIS45806B603
580, Black, 4000K	118-SIS45806B604