



SILO 60 SUSPENSION



FEATURES

- + Minimalist cylinder design, available in various colours and lengths
- + Sophisticated lens technology for enhanced visual comfort
- + Seamless canopy with quick connection for easy installation
- + Perfect for both individual use or as a cluster
- + Compatible with remote Casambi CBU-TED Bluetooth Controllable Dimmer (71-CASCBU)



GENERAL SPECIFICATIONS

LED	12W	
Lumens	1100 lm (3000K)	
Colour	3000K, Warm White 4000K, Cool White	
Efficacy	86.82 lm/w (3000K)	
Beam	60°	
Material	Powder Coated Aluminium	
CRI	92+	
Finish	White Black	
IP	20	
UGR	<15	
Colour Deviation	SDCM ≤2	
Lifetime	310,000hrs L70B10	
Additional Lens Options	15°	118-SIL6015
	24°	118-SIL6024
	36°	118-SIL6036
	45°	118-SIL6045
Warranty	5 Years	


PROJECT DETAILS

PROJECT:

TYPE:

NOTES:

DIMENSIONS (mm)



DRIVER SPECIFICATIONS

Power	300mA 240V Built-In Flicker Free Dimmable Driver
Dimming	Phase-Cut Dimming
Power Factor	>0.90

PRODUCT CODE

280, White, 3000K	118-SIP62812W603
280, White, 4000K	118-SIP62812W604
280, Black, 3000K	118-SIP62812B603
280, Black, 4000K	118-SIP62812B604
380, White, 3000K	118-SIP63812W603
380, White, 4000K	118-SIP63812W604
380, Black, 3000K	118-SIP63812B603
380, Black, 4000K	118-SIP63812B604
580, White, 3000K	118-SIP65812W603
580, White, 4000K	118-SIP65812W604
580, Black, 3000K	118-SIP65812B603
580, Black, 4000K	118-SIP65812B604