



FEATURES

- + Minimalist cylinder design, available in various colours and lengths
- + Sophisticated lens technology for enhanced visual comfort
- + Black baffle for reduced glare
- + Seamless canopy with quick connection for easy installation
- + Perfect for both individual use or as a cluster



GENERAL SPECIFICATIONS

LED	12W	
Lumens	1100 lm (3000K)	
Colour	<input type="checkbox"/> 3000K, Warm White <input type="checkbox"/> 4000K, Cool White	
Efficacy	86.82 lm/w (3000K)	
Beam	60°	
Material	Powder Coat Aluminium	
CRI	92+	
Finish	White Black	
IP	20	
Colour Deviation	SDCM ≥2	
Cable Length	2 metres	
Warranty	5 Years	
Accessories	Gold Baffle	118-SIL60GB
Additional Lens Options	15°	118-SIL6015
	24°	118-SIL6024
	36°	118-SIL6036
	45°	118-SIL6045


PROJECT DETAILS

PROJECT:

TYPE:

NOTES:

DIMENSIONS (mm)



DRIVER SPECIFICATIONS

Power	240V Built-In Flicker Free Driver
Dimming	Phase-Cut Dimming
Power Factor	>0.90

PRODUCT CODE

280, White, 3000K	118-SIP62812W603
280, White, 4000K	118-SIP62812W604
280, Black, 3000K	118-SIP62812B603
280, Black, 4000K	118-SIP62812B604
380, White, 3000K	118-SIP63812W603
380, White, 4000K	118-SIP63812W604
380, Black, 3000K	118-SIP63812B603
380, Black, 4000K	118-SIP63812B604
580, White, 3000K	118-SIP65812W603
580, White, 4000K	118-SIP65812W604
580, Black, 3000K	118-SIP65812B603
580, Black, 4000K	118-SIP65812B604