

PRO ROUND



The new generation Faze PRO downlight is specifically designed to enhance. Utilizing superior LED technology and with the highest CRI, these recessed ceiling lights are guaranteed to bring your spaces to life.

FEATURES

- + Precision reflector with clear lens for better light distribution
- + Specially designed heat sink for class leading heat dissipation.
- + IC-4 rated
- + Black baffle design eliminates glare for optimum visual comfort.
- + IP44 and suitable for wet areas.
- + Compatible with remote Casambi CBU-TED Bluetooth Controllable Dimmer (71-CASCBU) & with Casambi BasicDim Driver 13W (71-CAS350)



GENERAL SPECIFICATIONS LED 13W *operating wattage 14.8W 970 lm (3000K) | 1080 (4000K) Lumens 3000K, Warm White Colour 4000K, Cool White **Efficacy** 74 lm/w (3000K) | 83 lm/w (4000K) 15° | 24° | 36° | 60° **Beam** Powder Coat Aluminium Material 97+ CRI White | Black **Finish Colour Deviation** SDCM ≤2 Lifetime L70 >310,000hrs Warranty 7 Years

Please Note: When using C-Bus, use universal or trailing edge dimming modules


radiantlighting.

PROJECT DETAILS

PROJECT: TYPE:

NOTES:

DIMENSIONS (mm)



DRIVER SPECIFICATIONS

1	107	x W	12	v H	25	mm
_	107	X VV	45	ΧП	23	mm

Power	240V Remote
rower	Flicker Free
	Dimmable Driver
Dimming	Phase Cut Dimming
Power Factor	> 0.90

DALI dimming available upon request

ı	1	1		_			_	
-	-	J			ď	I	_	

White, 3000K, 60°	118-PR7LR13W603
White, 4000K, 60°	118-PR7LR13W604
Black, 3000K, 60°	118-PR7LR13B603
Black, 4000K, 60°	118-PR7LR13B604

B = E	FCTO	DCC	DEC

15° Reflector	118-RFLP15
24° Reflector	118-RFLP24
36° Reflector	118-RFLP36