# LITE MINI

The high-performance LITE MINI combines high lumen per watt efficacy and dynamic illumination. It also features a uniquely designed heat sink, for maximum heat dissipation in projects with minimum ceiling space.

- Precision reflector with clear lens – For better light distribution.
- Specially designed heat sink – For class leading heat dissipation.
- IP44 Rated – Suitable for wet areas.
- IC-4 Rated.
- > 55,000hrs L90B10 Lifetime.




| | |
|---|---|
| **DIMENSIONS** | W Ø85 mm H 49 mm |
| **CUT-OUT** | I Ø76mm |

## LUMINAIRE OPTIONS

**LED & LUMENS OPTIONS** (3000K | 4000K)

| | |
|---|---|
| **10W** 960lm \| 1040lm | **8W** 750lm \| 830lm |

**BEAM OPTIONS**

**60°** STANDARD **36°**

**FINISHES**

**WHITE** **BLACK**

## GENERAL SPECIFICATIONS

| | |
|---|---|
| **EFFICACY** | Up to 104 Lm/W |
| **COLOUR** | 3000K, Warm White<br>4000K, Cool White |
| **MATERIAL** | Powder Coated Material |
| **FINISH** | White \| Black |
| **CRI** | 92+ |
| **IP** | 44 |
| **COLOUR DEVIATION** | SDCM ≤2 |
| **UGR** | <19 |
| **LIFETIME** | > 55,000hrs L90B10 |
| **WARRANTY** | 5 Years |

## DRIVER SPECIFICATIONS

| | |
|---|---|
| **DIMENSIONS** | L 104 x W 43 x H 24mm |
| **POWER** | 250mA \| 200mA 240V<br>Remote Dimmable Driver |
| **DIMMING** | Phase Cut Dimming |
| **POWER FACTOR** | > 0.90 |

## PROJECT DETAILS

**PROJECT**

**TYPE**

**NOTES**

## PRODUCT CODES

| | |
|---|---|
| White, 3000K, 60° | **118-LI2M10W603** |
| White, 4000K, 60° | **118-LI2M10W604** |
| Black, 3000K, 60° | **118-LI2M10B603** |
| Black, 4000K, 60° | **118-LI2M10B604** |

## ACCESSORIES

| | |
|---|---|
| 36° Reflector | **118-RFLLM36** |

## DRIVER CODES

| | |
|---|---|
| 10W | **118-250MA** |
| 8W | **118-200MA** |

1300 438 609
fazelight.com