

ART T 250 MASK

By LOMBARDO


OUTDOOR + WALL

Also suitable for outdoor use. Integrated 220-240 V driver and latest-generation LED modules. White polycarbonate base, produced in-house via injection molding. Diffuser made of PMMA reinforced with impact-resistant elastomers and UV-resistant, chosen for its high transparency, long-term stability, and excellent resistance to yellowing. IP 66.

PROJECT

TYPE

NOTES



GENERAL SPECIFICATIONS

LED	16.5 W
LUMENS	1200 Lm
EFFICACY	72 Lm / W
COLOUR TEMPERATURE	2700K / 3000K / 4000K
MATERIAL	Polycarbonate
FINISH	White
CRI	80+
IP	66
IK RATING	07 2J xx5
WARRANTY	Available Upon Request
LIFETIME	50,000hrs L80B20
ORIGIN	Italy

POWER SPECIFICATIONS

DRIVER	Integrated, 220-240V
DIMMING	N/A
VOLTAGE	220-240V

PRODUCT CODES

WHITE, 3000K	48-LL116300W3
BLACK, 3000K	48-LL116300B3
DARK GREY, 3000K	48-LL116300E3
LIGHT GREY, 3000K	48-LL116300G3
CORTEN, 3000K	48-LL116300K3
SAND, 3000K	48-LL116300S3

2700K & 4000K CODES ARE AVAILABLE UPON REQUEST

MOTION SENSOR & DAY/NIGHT SENSOR AVAILABLE UPON REQUEST